

Ag/ZnO Silver Zinc Oxide

Manufacturing process and delivery forms

The material is manufactured by blending silver and zinc oxide powder, compacting, sintering, and extruding in the form of wire, profile and contact tips.

The latter are available with a brazable silver layer and, optionally, with an additional layer of brazing alloy.

Quality features of silver zinc oxide from Umicore

The components of the material are very evenly distributed. The material gets its excellent erosion resistance from the extreme level of compaction produced during the extrusion process.

Composition

Silver zinc oxide is available as Ag/ZnO 92/8 with 92 % silver by weight.

Tungsten oxide as an active component greatly improves the welding resistance in general purpose applications.

Key features

- » high resistance to welding on make
- » low contact resistance (comparable with other silver metal oxides)
- » low erosion in small current-limiting circuit breakers and motor-protection circuit breakers
- » free of toxic and carcinogenic components

Applications

- » earth-leakage circuit breaker
- » motor-protection circuit breaker
- » circuit breaker
- » general purpose relays
- » small contactors

Standard Composition

Ag/ZnO	ADDITIVE
SP	None
SPW	Tungsten Oxide

Microstructure

The zinc oxide particles are homogeneously distributed in the cross section. The directional forming during extrusion leads to a slight orientation of the zinc oxide particles in the longitudinal section.



Ag/ZnO 92/8 SPW cross section



Ag/ZnO 92/8 SPW longitudial section

GERMANY

Umicore AG & Co. KG Technical Materials Contact & Power Technology Materials Rodenbacher Chaussee 4 63457 Hanau Phone: +49 6181 59 4869 Fax: +49 6181 59 7 4869 cpm.sales@umicore.com

CHINA

Umicore Technical Materials Suzhou Co. Ltd. #508-2 Zhujiang Road, SND 215011 – Suzhou Phone: +86 512 6667 0800 Fax: +86 512 6667 3230 sales.utms@ap.umicore.com

BRAZIL

Umicore Brasil Ltda. Materiais Técnicos Rua Barão do Rio Branco, 368 Guarulhos-SP 07042-010 São Paulo Phone: +55 11 2421 1371 Fax: +55 11 2421 1180 info@tm-cpm.com.br

USA

Attleboro

Umicore Technical Materials North America Inc. 527 Pleasant Street, Building 11 Attleboro, MA 02703 Phone: +1 508 838 2064 Fax: +1 508 838 2062 sales.utmna@am.umicore.com

Glens Falls

Umicore Technical Materials North America Inc. 9 Pruyn's Island Drive Glens Falls, NY 12801 Phone: +1 518 932 0559 Fax: +1 518 792 3162 sales.utmna@am.umicore.com The information and statements contained herein are provided free of charge and are for general information purposes only. They are believed to be accurate at the time of publication, but Umicore makes no representations or warranty of any kind with respect thereto, express or implied, about the completeness, accuracy, reliability, suitability or availability. Use or application of such information or statements is at the user's discretion, without any liability on the part of Umicore. Nothing herein shall be constructed as a license or recommendation to use. Umicore reserves the right to alter any product or service at its own discretion. All sales are subject to Umicore's General Terms and Conditions of Sale and Delivery (http://www.umicore.de/service/agbs/agbs.htm).